

Daikin Emura FTXJ

Zidna jedinica | Hlađenje, grijanje, pročišćavanje zraka



R-32

do A+++

do A+++

Učinkovitost	Rad	Pročišćavanje zraka	Protok zraka	Upravljanje i određivanje rasporeda	Ostalo
	   	   	 	 	

uključeno

Cijene		FTXJ20AW + RXJ20A	FTXJ25AW + RXJ25A	FTXJ35AW + RXJ35A	FTXJ42AW + RXJ42A	FTXJ50AW + RXJ50A
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	KM 4.350,-	4.590,-	5.370,-	6.400,-	7.020,-
	Cijena unutarnje jedinice	KM 1.680,-	1.770,-	2.130,-	2.510,-	2.650,-
	Cijena vanjske jedinice	KM 2.670,-	2.820,-	3.240,-	3.890,-	4.370,-
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	KM 3.718,-	3.923,-	4.590,-	5.470,-	6.000,-
	Cijena unutarnje jedinice	KM 1.436,-	1.513,-	1.821,-	2.145,-	2.265,-
	Cijena vanjske jedinice	KM 2.282,-	2.410,-	2.769,-	3.325,-	3.735,-

Cijene		FTXJ20AS + RXJ20A	FTXJ25AS + RXJ25A	FTXJ35AS + RXJ35A	FTXJ42AS + RXJ42A	FTXJ50AS + RXJ50A
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	KM 4.390,-	4.770,-	5.570,-	6.870,-	7.270,-
	Cijena unutarnje jedinice	KM 1.720,-	1.950,-	2.330,-	2.980,-	2.900,-
	Cijena vanjske jedinice	KM 2.670,-	2.820,-	3.240,-	3.890,-	4.370,-
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	KM 3.752,-	4.077,-	4.761,-	5.872,-	6.214,-
	Cijena unutarnje jedinice	KM 1.470,-	1.667,-	1.991,-	2.547,-	2.479,-
	Cijena vanjske jedinice	KM 2.282,-	2.410,-	2.769,-	3.325,-	3.735,-

Cijene		FTXJ20AB + RXJ20A	FTXJ25AB + RXJ25A	FTXJ35AB + RXJ35A	FTXJ42AB + RXJ42A	FTXJ50AB + RXJ50A
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	KM 4.310,-	4.610,-	5.480,-	6.650,-	7.150,-
	Cijena unutarnje jedinice	KM 1.640,-	1.790,-	2.240,-	2.760,-	2.780,-
	Cijena vanjske jedinice	KM 2.670,-	2.820,-	3.240,-	3.890,-	4.370,-
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	KM 3.684,-	3.940,-	4.684,-	5.684,-	6.111,-
	Cijena unutarnje jedinice	KM 1.402,-	1.530,-	1.915,-	2.359,-	2.376,-
	Cijena vanjske jedinice	KM 2.282,-	2.410,-	2.769,-	3.325,-	3.735,-

Energetska učinkovitost		FTXJ/RXJ	20AW/S/B + 20A	25AW/S/B + 25A	35AW/S/B + 35A	42AW/S/B + 42A	50AW/S/B + 50A
Rashladni učin	Min./Nom./Max.	kW	1,3/2,0/2,6	1,3/2,5/3,2	1,4/3,4/4,0	1,7/4,2/5,0	1,7/5,0/5,3
Učin grijanja	Min./Nom./Max.	kW	1,3/2,5/3,5	1,3/2,8/4,7	1,4/4,0/5,2	1,7/5,4/6,0	1,7/5,8/6,5
Priključna snaga	Hlađenje	Nom.	kW 0,43	0,56	0,78	1,05	1,36
	Grijanje	Nom.	kW 0,50	0,56	0,99	1,31	1,45
Hlađenje	Oznaka energetske učinkovitosti			A+++		A++	
	Učin	Pdesign	kW 2,0	2,5	3,4	4,2	5,0
	SEER		8,75	8,74	8,73	7,5	7,33
	Oznaka energetske učinkovitosti	kWh/a	80	100	136	196	239
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti			A+++		A++	
	Učin	Pdesign	kW 2,40	2,45	2,50	3,80	4,00
	SCOP			5,15		4,60	
	Oznaka energetske učinkovitosti	kWh/a	652	666	680	1.156	1.218

Tehnički podaci - unutarnja jedinica				FTXJ	20AW/S/B	25AW/S/B	35AW/S/B	42AW/S/B	50AW/S/B
Dimenzije	Jedinica	Visina x Širina x Dubina	mm				305x900x212		
Filter za zrak	Tip						Uklonjiv/periv		
Razina zvučnog tlaka	Hlađenje	Tihi/Niski/Srednji/Visoki	dBa	19/25/32/39	19/25/33/40	19/25/33/41	21/29/37/45	24/31/39/46	
	Grijanje	Tihi/Niski/Srednji/Visoki	dBa	19/25/32/39	19/25/33/40	19/25/33/41	21/29/37/45	24/33/42/46	

Tehnički podaci - vanjska jedinica				RXJ	20A	25A	35A	42A	50A
Dimenzije	Jedinica	Visina x Širina x Dubina	mm			552x840x350		734x954x408	
Razina zvučnog tlaka	Hlađenje	Nom.	dBa		46		49	48	
	Grijanje	Nom.	dBa		47		49	48	49
Radno područje	Hlađenje	Okolina	Min.~Max.	°CDB			-10~50		
	Grijanje	Okolina	Min.~Max.	°CDB			-20~24		
Radna tvar	Tip/ GWP/ Punjenje		kg/TCO _{Eq}			R-32/675/0,76/0,52		R-32/675/1,10/0,75	
Dimenzije priključka	Duljina cijevi	OU - IU	Max.	m		20		30	
	Visinska razlika	IU - OU	Max.	m		15		20	
Električno napajanje	Faza / Preporučeni osigurač (MFA)		A		1~/10			1~/13	