

Perfera W FTXM

Zidna jedinica | Hlađenje, grijanje, pročišćavanje zraka

R-32

do
A+++

do
A+++


FTXM-A



RXM-A



uključeno

Učinkovitost	Rad	Pročišćavanje zraka	Protok zraka	Upravljanje i određivanje rasporeda	Ostalo functions
				uključeno	

Cijene		CTXM15A	FTXM20A + RXM20A	FTXM25A + RXM25A	FTXM35A + RXM35A	FTXM42A + RXM42A	FTXM50A + RXM50A	FTXM60R + RXM60R	FTXM71R + RXM71R	
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	KM	-	3.070,-	3.270,-	3.910,-	4.460,-	4.790,-	5.650,-	6.760,-
	Cijena unutarnje jedinice	KM	1.070,-	1.140,-	1.230,-	1.460,-	1.570,-	1.710,-	1.990,-	2.230,-
	Cijena vanjske jedinice	KM	-	1.930,-	2.040,-	2.450,-	2.890,-	3.080,-	3.660,-	4.530,-
	Cijena seta (unutarnja + vanjska jedinica)	KM	-	2.624,-	2.795,-	3.342,-	3.812,-	4.094,-	4.829,-	5.778,-
bez PDV-a	Cijena unutarnje jedinice	KM	915,-	974,-	1.051,-	1.248,-	1.342,-	1.462,-	1.701,-	1.906,-
	Cijena vanjske jedinice	KM	-	1.650,-	1.744,-	2.094,-	2.470,-	2.632,-	3.128,-	3.872,-

Energetska učinkovitost	FTXM + RXM	CTXM15A	20A + 20A	25A + 25A	35A + 35A	42A + 42A	50A + 50A	60R + 60R	71R + 71R
Rashladni učin	Min./Nom./Max.	kW	0,9/2,0/3,0	0,9/2,5/3,8	0,9/3,5/4,4	1,5/4,2/5,2	1,7/5,0/5,3	1,7/6,0/7,0	2,3/7,1/8,5
Učin grijanja	Min./Nom./Max.	kW	0,8/2,5/4,5	0,8/2,8/5,0	0,8/4,0/5,2	1,5/5,4/5,7	1,7/5,8/6,5	1,7/7,0/8,0	2,3/8,2/10,2
Priključna snaga	Hlađenje	Nom.	0,37	0,48	0,76	1,00	1,36	1,77	2,34
	Grijanje	Nom.	0,50	0,56	0,88	1,29	1,40	1,94	2,57
Hlađenje	Oznaka energetske učinkovitosti			A+++		A+++		A+++	
	Učin	Pdesign	2,00	2,50	3,50	4,20	5,00	6,00	7,10
	SEER			9,47		9,25	8,11	6,90	6,20
	Oznaka energetske učinkovitosti	kWh/a	74	92	132	181	224	304	401
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti			A+++		A+++		A+++	
	Učin	Pdesign	2,30	2,40	2,50	4,00	4,50	4,80	6,20
	SCOP/A			5,20		5,00		4,30	4,10
	Oznaka energetske učinkovitosti	kWh/a	619	647	673	1.120	1.312	1.562	2.117

Tehnički podaci - unutarnja jedinica			FTXM	CTXM15A	20A	25A	35A	42A	50A	60R	71R
Dimenzije	Jedinica	Visina x Širina x Dubina	mm	298x804x252						299x998x292	
Filter za zrak	Tip			Uklonjiv/periv							
Razina zvučnog tlaka	Hlađenje	Tihi/Niski/Srednji/Visoki	dBA	19/25/33/41			19/29/37/45	21/30/38/45	27/33/40/44	30/37/42/46	32/38/43/47
	Grijanje	Tihi/Niski/Srednji/Visoki	dBA	20/26/34/39		20/27/34/39	20/28/35/39	21/29/37/45	31/34/41/46	33/36/41/45	34/37/42/46

Tehnički podaci - vanjska jedinica	RXM	20A	25A	35A	42A	50A	60R	71R
Dimenzije	Jedinica	Visina x Širina x Dubina	mm	610x923x367			734x954x401	734x954x401
Razina zvučnog tlaka	Hlađenje	Nom.	dBA	46	47	48	48	47
	Grijanje	Nom.	dBA	47		49	49	48
Radno područje	Hlađenje	Okolina	Min.-Max.	-10~-50°C			-10~-46°C	
	Grijanje	Okolina	Min.-Max.	-20~-24°C			-15~-24°C	
Radna tvar	Tip / GWP / Punjenje	kg / TCO _{Eq}		R-32/675/0,95/0,64			R-32/675/1,10/0,74	R-32/675/1,15/0,776
Dimenzije priključka	Duljina cijevi	OU - IU	Max.	20			30	
	Visinska razlika	IU - OU	Max.	15			20	
Električno napajanje	Faza / Preporučeni osigurač (MFA)	A		1~/10	1~/13		1~/16	1~/20