

Sensira FTXC

Zidna jedinica | Hlađenje i grijanje



FTXC-D



RXC-D



ARC486A2



BRP069B45

R-32

do
A++

do
A+


Cijene		FTXC20D + RXC20D	FTXC25D + RXC25D	FTXC35D + RXC35D	FTXC50D + RXC50D	FTXC60D + RXC60D	FTXC71D + RXC71D
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	KM 1.350,-	1.450,-	1.590,-	2.350,-	2.800,-	3.850,-
	Cijena unutarnje jedinice	KM 450,-	490,-	540,-	790,-	930,-	1.290,-
	Cijena vanjske jedinice	KM 900,-	960,-	1050,-	1.560,-	1.870,-	2.560,-
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	KM 1.154,-	1.239,-	1.359,-	2.009,-	2.393,-	3.291,-
	Cijena unutarnje jedinice	KM 385,-	419c	462,-	675,-	795,-	1.103,-
	Cijena vanjske jedinice	KM 769,-	821,-	897,-	1.333,-	1.598,-	2.188,-

Energetska učinkovitost		FTXC + RXC	20D + 20D	25D + 25D	35D + 35D	50D + 50D	60D + 60D	71D + 71D
Rashladni učin	Min./Rated/Max.	kW	1,3/2,0/3,0	1,3/2,5/3,0	1,3/3,5/4,0	1,4/5,1/6,2	1,8/6,2/7,0	2,3/7,1/7,3
Učin grijanja	Min./Rated/Max.	kW	1,3/2,5/4,0	1,3/2,8/4,0	1,3/4,0/4,8	1,4/5,6/6,6	1,5/6,4/8,0	2,3/8,0/9,0
Prikjučna snaga	Hlađenje	Min./Nom./Max.	kW 0,30/0,60/1,15	0,30/0,77/1,15	0,32/1,05/1,74	0,30/1,55/2,11	0,38/1,89/2,05	0,44/2,38/2,54
	Grijanje	Min./Nom./Max.	kW 0,28/0,67/1,35	0,28/0,75/1,35	0,28/1,07/1,57	0,27/1,52/1,85	0,33/1,68/2,35	0,50/2,46/2,74
Hlađenje	Oznaka energetske učinkovitosti				A++			A++
	Učin Pdesign	kW	2,08	2,57	3,44	5,08	6,21	6,96
	SEER		6,89	6,84	6,87	6,45	6,40	5,30
	Oznaka energetske učinkovitosti	kWh/a	106	131	175	276	339	460
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti				A+			A+
	Učin Pdesign	kW	1,87	2,23	2,24	3,90	4,10	6,35
	SCOP/A		4,40	4,45	4,28	4,42	4,24	3,81

Tehnički podaci - unutarnja jedinica			FTXC	20D	25D	35D	50D	60D	71D
Dimenzije	Jedinica	Visina x Širina x Dubina	mm	288x770x234				297x990x273	
Filter za zrak	Tip			Uklonjiv/periv					
Ventilator – protok zraka	Hlađenje	Tihi/Niski/Srednji/Visoki	m³/min	5,4/6,1/8,1/10,8		5,4/6,4/8,7/11,1		7,4/8,2/9,9/12,5	
								10,2/12,5/14,5/20,4	
Razina zvučnog tlaka	Hlađenje	Tihi/Niski/Srednji/Visoki	dBA	21/26/33/40		22/26/34/41		30/33/39/47	
								31/38/42/48	

Tehnički podaci - vanjska jedinica				RXC	20D	25D	35D	50D	60D	71D
Dimenzije	Jedinica	Visina x Širina x Dubina		mm	550x658x273			615x845x300		695x930x350
Razina zvučnog tlaka	Hlađenje	Visoki		dBA	45		46	51	54	
Radno područje	Hlađenje	Okolina	Min.~Max.	°CDB	10~46			-10~46		
	Grijanje	Okolina	Min.~Max.	°CDB	-15~24					
Radna tvar	Tip / GWP / Punjenje		kg / TCO _{Eq}		R-32/675/0,55/0,371		R-32/675/0,75/0,506	R-32/675/1,00/0,675	R-32/675/1,10/0,743	R-32/675/1,15/0,776
Dimenzije priključka	Duljina cijevi	OU - IU	Max.	m	20			30		
	Sustav		Prednapunjeno	m	8					
	Visinska razlika		IU - OU	Max.	m	15			20	
Električno napajanje	Faza / Preporučeni osigurač (MFA)			A	1~/16					