

Sensira FTXF

Zidna jedinica | Hlađenje i grijanje



FTXF-E



RXF-E



ARC470A1



BRP069B45/BRP069C47*

R-32

do
A++

do
A+

Učinkovitost	Rad	Pročišćavanje zraka	Upravljanje i određivanje rasporeda	Ostalo
			opcija	

Cijene		FTXF20E + RXF20E	FTXF25E + RXF25E	FTXF35E + RXF35E	FTXF42E + RXF42E	FTXF50D + RXF50D	FTXF60D + RXF60D	FTXF71D + RXF71D
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	KM	1.550,-	1.650,-	1.790,-	2.150,-	2.650,-	3.200,-
	Cijena unutarnje jedinice	KM	500,-	540,-	600,-	700,-	880,-	1.060,-
	Cijena vanjske jedinice	KM	1.050,-	1.110,-	1.190,-	1.450,-	1.770,-	2.140,-
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	KM	1.325,-	1.410,-	1.530,-	1.838,-	2.265,-	2.735,-
	Cijena unutarnje jedinice	KM	427,-	462,-	513,-	598,-	752,-	906,-
	Cijena vanjske jedinice	KM	897,-	949,-	1.017,-	1.239,-	1.513,-	1.829,-

Energetska učinkovitost		FTXF + RXF	20E + 20E	25E + 25E	35E + 35E	42E + 42E	50D + 50D	60D + 60D	71D + 71D
Rashladni učin	Min./Nom./Max.	kW	1,3/2,0/2,4	1,3/2,5/2,8	1,3/3,3/3,8	1,4/4,2/4,3	1,7/5,0/6,0	1,7/6,0/7,0	2,3/7,1/7,3
Učin grijanja	Min./Nom./Max.	kW	1,3/2,4/3,3	1,3/2,8/3,7	1,3/3,5/4,4	1,4/4,6/5,0	1,7/6,0/7,7	1,7/6,4/8,0	2,3/8,2/9,0
Priključna snaga	Hlađenje	Min./Nom./Max.	kW	0,31/0,59/0,72	0,31/0,77/1,05	0,31/1,00/1,40	0,31/1,27/1,50	-1,50/-	-1,85/-
	Grijanje	Min./Nom./Max.	kW	0,25/0,64/0,95	0,25/0,75/1,11	0,25/0,94/1,50	0,25/1,24/1,40	-1,62/-	-1,63/-
Hlađenje	Oznaka energetske učinkovitosti					A++			A
	Učin	Pdesign	kW	2,00	2,50	3,50	4,20	5,00	6,00
	SEER				6,50		6,21	6,15	5,15
	Oznaka energetske učinkovitosti	kWh/a	108	135	188	226	282	342	483
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti					A+			A
	Učin	Pdesign	kW	2,20	2,40	2,60	3,30	4,60	4,80
	SCOP/A			4,20		4,30		4,06	3,81
	Oznaka energetske učinkovitosti	kWh/a	733	801	867	1.075	1.585	1.654	2.275

Tehnički podaci - unutarnja jedinica			FTXF	20E	25E	35E	42E	50D	60D	71D
Dimenzije	Jedinica	Visina x Širina x Dubina	mm	286x770x225				295x990x263		
Filter za zrak	Tip			Uklonjiv/periv						
Razina zvučnog tlaka	Hlađenje	Tihi/Niski/Srednji/Visoki	dBA	20/25/33/39	20/26/33/40	20/27/34/43	22/30/36/45	31/34/39/43	33/36/41/45	34/37/42/46
	Grijanje	Tihi/Niski/Srednji/Visoki	dBA	21/28/34/39	21/28/34/40	21/29/35/40	22/28/34/44	30/33/38/42	32/35/40/44	33/36/41/45

Tehnički podaci - vanjska jedinica			RXF	20E	25E	35E	42E	50D	60D	71D
Dimenzije	Jedinica	Visina x Širina x Dubina	mm	556x740x343				734x870x373		
Razina zvučnog tlaka	Hlađenje	Nom./Visoki	dBA	-46		-48		47/-	49/-	52/-
	Grijanje	Nom./Visoki	dBA	-47		-48		49/-		52/-
Radno područje	Hlađenje	Okolina Min.~Max.	°CDB	-10 ~48						
	Grijanje	Okolina Min.~Max.	°CDB	-15~24						
Radna tvar	Tip / GWP / Punjenje		kg /TCO _{Eq}	R-32/675/0,42/0,28		R-32/675/0,55/0,37		R-32/675/0,75/0,51	R-32/675/0,90/0,61	R-32/675/1,15/0,78
Dimenzije priključka	Duljina cijevi	OU - IU Max.	m	20				30		
	Visinska razlika	IU - OU Max.	m	12				20		
Električno napajanje	Phase/Maximum fuse amps (MFA)		A	1~16				1~20		

*BRP069C47 - WiFi adapter za jedinice FTXF-E; BRP069B45 - WiFi adapter za FTXF-D