

Ururu Sarara FTXZ

Zidna jedinica | Hlađenje, grijanje, pročišćavanje zraka, ventilacija, ovlaživanje i odvlaživanje

R-32

do
A+++

do
A+++



FTXZ-N



RXZ-N



ARC477A1



BRP069B42

Učinkovitost	Rad	Pročišćavanje zraka	Protok zraka	Kontrola vlažnosti	Upravljanje i određivanje rasporeda	Ostalo
    	   			 	 	
			samo hlađenje		opcija	-20°

Cijene		FTXZ25N + RXZ25N	FTXZ35N + RXZ35N	FTXZ50N + RXZ50N
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	KM 6.630,-	KM 6.980,-	KM 8.200,-
	Cijena unutarnje jedinice	KM 2.300,-	KM 2.470,-	KM 2.870,-
	Cijena vanjske jedinice	KM 4.330,-	KM 4.510,-	KM 5.330,-
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	KM 5.667,-	KM 5.966,-	KM 7.009,-
	Cijena unutarnje jedinice	KM 1.966,-	KM 2.111,-	KM 2.453,-
	Cijena vanjske jedinice	KM 3.701,-	KM 3.855,-	KM 4.556,-

Energetska učinkovitost	FTXZ + RXZ	25N + 25N	35N + 35N	50N + 50N
Rashladni učin	Min./Nom./Max. kW	0,6/2,5/3,9	0,6/3,5/5,3	0,6/5,0/5,8
Učin grijanja	Min./Nom./Max. kW	0,6/3,6/7,5	0,6/5,0/9,0	0,6/6,3/9,4
Priključna snaga	Hlađenje Min./Nom./Max. kW	0,11/0,41/0,88	0,11/0,66/1,33	0,11/1,10/1,60
	Grijanje Min./Nom./Max. kW	0,10/0,62/2,01	0,10/1,00/2,53	0,10/1,41/2,64
Hlađenje	Oznaka energetske učinkovitosti	A+++	A+++	A+++
	Učin Pdesign kW	2,50	3,50	5,00
	SEER	9,54	9,00	8,60
	Oznaka energetske učinkovitosti kWh/a	92	136	203
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti	A+++	A+++	A+++
	Učin Pdesign kW	3,50	4,50	5,60
	SCOP/A	5,90	5,73	5,50
	Oznaka energetske učinkovitosti kWh/a	831	1.100	1.427

Tehnički podaci - unutarnja jedinica	FTXZ	25N	35N	50N
Dimenzije	Jedinica Visina x Širina x Dubina	mm	295x798x372	
Filter za zrak	Tip		Samočisteći filter	
Razina zvučnog tlaka	Hlađenje Tihi/Niski/Srednji/Visoki	dBA	19/27/35/42	23/30/38/47
	Grijanje Tihi/Niski/Srednji/Visoki	dBA	19/29/36/42	24/31/38/44

Tehnički podaci - vanjska jedinica	RXZ	25N	35N	50N
Dimenzije	Jedinica Visina x Širina x Dubina	mm	693x795x300	
Razina zvučnog tlaka	Hlađenje Visoki	dBA	48	49
	Grijanje Visoki	dBA	48	50
Radno područje	Hlađenje Okolina Min.-Max. °CDB		-10~43	
	Grijanje Okolina Min.-Max. °CDB		-20~24	
Radna tvar	Tip / GWP / Punjenje	kg / TCOEq	R-32/675/1,34/0,9	
Dimenzije priključka	Duljina cijevi OU - IU Max.	m	10	
	Visinska razlika IU - OU Max.	m	8	
Električno napajanje	Faza / Preporučeni osigurač (MFA)	A	1~ /16	