

Wall mounted unit

ATXP-M + ARXP-M



BLUEEVOLUTION *Siesta*

DAIKIN



Daikin Residential Controller



Energy saving during standby mode



3-D air flow



Multi model application

Discreet Siesta wall mounted unit providing high efficiency and comfort

- › Practically inaudible
- › Daikin residential controller via app
- › Voice control
- › 3-D airflow: air is blown into all corners of a room
- › Ideal for above door installation

- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

ATXP-M + ARXP-M



ATXP20-35M



ARXP25-35M



ARC480A11

Indoor unit			ATXP	20M	25M	35M
Dimensions	Unit	HeightxWidthxDpth	mm	286 x770 x225		
Weight	Unit		kg	8.50		9.00
Air filter	Type			Removable / washable		
Fan	Air flow rate	Cooling	Silent operation/Low/ Medium/High m ³ /min	4.2 /5.6 /7.4 /9.5		4.2 /5.8 /7.7 /9.7
		Heating	Silent operation/Low/ Medium/High m ³ /min	5.2 / 6.2 / 8.1 / 10.4		5.2 / 6.4 / 8.1 / 10.4
Sound power level	Cooling		dBA	55		58
	Heating		dBA	55		58
Sound pressure level	Cooling	Silent operation/Low/High	dBA	19 /25 /39		20 /27 /43
	Heating	Silent operation/Low/High	dBA	21 /28 /39		21 /29 /40
Control systems	Infrared remote control			ARC480A53		
	Wired remote control			BRC944B2 / BRC073A1		


Outdoor unit			ARXP	20M	25M	35M
Dimensions	Unit	HeightxWidthxDpth	mm	550 x658 x275		
Weight	Unit		kg	26		28
Sound power level	Cooling		dBA	60		62
	Heating		dBA	61		62
Sound pressure level	Cooling	High	dBA	46		48
	Heating	High	dBA	47		48
Operation range	Cooling	Ambient	Min.-Max. °CDB	-10~46		
	Heating	Ambient	Min.-Max. °CWB	-15~18		
Refrigerant	Type			R-32		
	GWP			675.0		
Piping connections	Charge		kg/TCO2Eq	0.55 /0.37		0.70 /0.48
	Liquid	OD	mm	635		
	Gas	OD	mm	9.5		
	Piping length	OU - IU	Max. m	15		
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)		
	Level difference	IU - OU	Max. m	12		
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50 /220-240		
Current - 50Hz	Maximum fuse amps (MFA)		A	16		

See separate drawing for operation range | See separate drawing for electrical data | Contains fluorinated greenhouse gases

Efficiency data			ATXP + ARXP	20M + 20M	25M + 25M	35M + 35M
Cooling capacity	Min./Nom./Max.		kW	1.3 /2.00 /2.6		1.3 /2.50 /3.0
Heating capacity	Min./Nom./Max.		kW	1.30 /2.50 /3.50		1.30 /3.00 /4.00
Power input	Cooling	Min./Nom./Max.	kW	0.31 /0.50 /0.72		0.31 /0.66 /0.72
	Heating	Min./Nom./Max.	kW	0.25 /0.52 /0.95		0.25 /0.69 /0.95
Space cooling	Energy efficiency class			A++		
	Capacity	Pdesign	kW	2.00		2.50
	SEER			6.77		6.85
	Annual energy consumption		kWh/a	104		128
Space heating (Average climate)	Energy efficiency class			A++		
	Capacity	Pdesign	kW	2.20		2.40
	SCOP/A			4.64		4.60
	Annual energy consumption		kWh/a	663		730
Nominal efficiency	EER			3.98		3.79
	COP			4.77		4.36
	Energy labeling Directive	Cooling/Heating		A/A		

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for electrical data

Daikin Europe N.V. Naamloze Venootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN21-047

01/2021



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.